

HAND TOSS



FLATBED



DRUM



TRIPLE FLIP



SUPERFLEX

PREDUSTER/BREADER

**Multiple Functions
One Machine**



**Hooded for
Dust Control**


www.nothum.com +1-417-831-2816

NOTHUM
FOOD PROCESSING SYSTEMS

SuperFlex GENERAL SPECIFICATIONS

	SF 14	SF 24	SF 40 HP
Length O/A	All Models - 3454mm		
Width O/A	1092mm	1346mm	1702mm
Height O/A	1575mm / 1956mm		1753mm / 2108mm
Infeed Height	All Models - 940mm to 1016mm		
Discharge Height	All Models - 940mm to 1016mm		
Actual Belt Width	406mm	660mm	1016mm
Electrical	208-240 VAC 3pH-30AMP / 380-480 VAC 3pH- 20AMP		

ALL MODELS



Specifications are approximate and subject to change

Save money & Create quick ROI

- Decrease labor and breading losses
- Eliminate redundant equipment

AcuFeeder
91 kilogram bulk
feed hopper

Coating Versatility

Variety of Breadings and
Predusts:

- Flour
- Crumb
- Seasonings
- Sugars
- And many others

Technology

- All setting can be saved in an onboard recipe
- Automatic Feed System
- Automatic spreading to full belt-width



NOTHUM.COM

nothum@nothum.com • +1-417-831-2816 • 631 South Kansas, Springfield, Missouri 65802 USA

Nothum's equipment, concepts and processes may be covered by one or more US and/or international patents. Other US and/or international patents pending.